

## Fire Protection for Multi-Family Applications



**P:** (780) 612- 7740 **E:** info@barriertek.com

A World Without Catastrophic Fire

## Multi-Family Product Information

Table of Contents -01-


ProTEKtor IID<sup>®</sup> 02 Technical Data Sheets Safety Data Sheets

ProTEKtor IIJ® 03 Technical Data Sheets Safety Data Sheets

ProTEKtor (PG)® 04 Technical Data Sheets Safety Data Sheets

AtTEK<sup>®</sup> 05

Technical Data Sheets Safety Data Sheets



## **ProTEKtor IID**®

#### **Technical Data Sheets**





# **ProTEKtor IID**®

## **Technical Data Sheet**

### **Intumescent Latex Paint**

#### **Intended Uses:**

<b>01</b> 02	A fire-resistant and preserving inorganic borate designed for use with dimensional lumber to reduce flame spread, smoke development, and deterioration of wood.
03	Product Description:
04	An inorganic borate solution with termiticide, insecticide, fungicide, and fire resistant properties.
05	

Date of Issue:

January 21, 2021

<b>Finish:</b> Clear	Standard Colours: Green or Blue	
Tint Range:	Secondary Colours:	
N/A	N/A	
Required Coverage:	Typical Volume Solids:	
15 grams / ft <sup>2</sup>	10%	
Recommended # of Coats:	Typical Specific Gravity:	
1 at recommended coverage	1.1	
Flash Point:	Application Thinner:	
N/A	DO NOT THIN	

Flame Spread Index: 20 (CAN/ULC S102)

Smoke Development Index: 10 (CAN/ULC S102)

#### **Surface Preparation**

Surfaces must be clean, dry, and free of dust and other debris. Remove any loose substrate pieces (i.e. wood, peeling paint). When treating bare wood surfaces with the intent of fire protection, no priming is required.

#### Application

Brush, roller, or suitable heavy-duty airless sprayer. (Recommended tips are .20-.30 inches.)

Dry times at 21°C and 50% (+ or – 10) R.H. **To Touch:** 45 minutes – 2 hours **To Handle:** 3 – 5 hours **To Overcoat:** 6 hours minimum

#### **Additional Data**

For optimum adhesion and application performance, ensure that the temperature and relative humidity are between 15 and 25°C and 40-60% respectively, at the time of application and for four hours afterward.

The information provided is accurate and true to the best of our knowledge. However, no guarantee or warranty of any kind, expressed or implied, is given when the product is not applied by certified BarrierTek Inc. installers.

## **ProTEKtor IID**®

Safety Data Sheet

## **01** Identification

**Product Name: ProTEKtor IID® Product Code:** \_\_\_\_ **Product Use: Fire Retardant** Manufacturer's Name: **Genics Inc.** 561 Acheson Rd. 53016 Hwy 60 Acheson, AB, Canada T7X 5A7 **BarrierTek Phone:** (780) 612-7740 In case of hazardous materials or dangerous goods **Emergency Phone:** incident, spill, leak, fire, exposure, or accident, call CHEMTREC 24 hours at 1-800-242-9300 or 1-703-527-3887. **SDS Preparation Date:** January 2021

05

01

02

03

### Hazard Identification Toxicological Properties

Emergency Overview:	ProTEKtor IID <sup>®</sup> is a clear or dyed (blue, green or orange), odorless liquid that is not flammable, combustible, or explosive and has low acute oral and dermal toxicity.	05
Potential Ecological Effects:	Large amounts of ProTEKtor IID® can be harmful to plants and other species. Therefore, releases into the environment should be minimized.	
Routes of Exposure		
Inhalation:	Occasional mild irritation to nose and throat may occur from inhalation of ProTEKtor IID <sup>®</sup> . Avoid producing very fine mists.	
Eye Contact:	ProTEKtor IID <sup>®</sup> is non-irritating to eyes in normal use.	
Skin Contact:	ProTEKtor IID <sup>®</sup> does not cause irritation to intact skin. Dermal exposure is not a concern because ProTEKtor IID <sup>®</sup> is poorly absorbed through intact skin.	
Ingestion:	Products containing ProTEKtor IID® are not intended for ingestion. ProTEKtor IID® has a low acute toxicity. Small amounts (e.g. a teaspoonful) swallowed accidentally are not likely to cause effects; swallowing amounts larger than one teaspoon may cause gastrointestinal symptoms.	
Cancer:	ProTEKtor IID <sup>®</sup> is not a known carcinogen.	

Signs and SymptomsSymptoms of accidental overexposure to ProTEKtor01of Exposure:IID® might include nausea, vomiting, and diarrhea,<br/>with delayed effects of skin redness and peeling.02These symptoms have been associated with the<br/>accidental overexposure to the chemically-related03substance boric acid by ingestion or absorption<br/>through large areas of damaged skin.04

Refer to Section 11 for details on toxicological data.

## **03** Composition / Information on Ingredients

Ingredients	CAS #	% Percent (by weight)	Hazard Classification
Disodium Octaborate Tetrahydrate	12290-03-4	8-12	-



### **Fire-Fighting Measures**

General Hazard:	None, because ProTEKtor IID <sup>®</sup> is not flammable	04
Flammability classification (29 CFR 1910.1200):	Not combustible or explosive. The product is itself a flame retardant.	05
Extinguishing Media :	Any fire extinguishing media may be used on nearby fires.	

## 

### **Accidental Release Measures**

General:	ProTEKtor IID <sup>®</sup> is a clear or dyed (blue, green, or orange)
	liquid that may, at high concentrations, cause damage to
	trees or vegetation by root absorption. (Refer to
	Ecological information, Section 12, for specific
	information.)
Land Spill:	Absorb ProTEKtor IID <sup>®</sup> with hydrophilic absorbent and
	place in containers for disposal in accordance with
	applicable local regulations. Avoid contamination of
	water bodies during cleanup and disposal.

Spillage Into Water:	Where possible, remove any intact containers from	
	the water. Advise local water authorities that none of	
	the affected water should be used for irrigation or as	02
	potable water until natural dilution returns the	
	boron value to its normal environmental	03
	background level. (Refer to Sections 12, 13, and 15	
	for additional information.)	04
Additional Notes:	ProTEKtor IID <sup>®</sup> is a non-hazardous waste when	05
	spilled or disposed of, as defined in the Resource	
	Conservation and Recovery Act (RCRA) regulations	
	(40 CFR 261). (Refer to Regulatory information,	
	Section 15, for additional references.)	

## 07

### Handling and Storage Procedures

Work and Hygiene	If during use of this product, dusts or particulates are
Practices:	generated, avoid breathing, and avoid skin or eye
	contact. Use ventilation and other engineering
	controls to minimize creation and exposure to dusts
	generated by this product.
Storage and Handling	Store this product in properly labeled, closed
Practices:	containers in a cool, dry location away from sources
	of intense heat. Store away from incompatible
	materials. (See Stability and Reactivity).

Protective Practices Ensuring Maintenance	Follow practices indicated in Accidental Release Measures. Make certain that application	01
of Contaminated Equipment:	equipment is locked and tagged-out safely, as necessary.	02
		03
General Storage Temperature:	Dry, indoor storage between 5°C and 35°C is recommended. Ambient recommended. Keep containers tightly closed.	04 05
Storage	Atmospheric	

08

### Exposure Controls: Personal Protection

**Pressure:** 

Engineering Control:	N/A
Control Factor:	N/A
Personal Respirators:	N/A
Skin Protection:	Wear protective gloves.
Eye Protection:	Wear safety glasses or goggles.

### **Physical and Chemical Properties**

		04
Colour:	Green or Blue	04
Odor:	N/A	~=
Safety Data:	Flash Point: N/A	05
	Ignition temperature: N/A	
	Self-ignition temperature: N/A	
	Lower explosion limit: N/A	
	Upper explosion limit: N/A	
Solubility:	Water miscible	
Specific Gravity:	1.1g/mL	
Vapour Pressure:	Negligible at 20°C	
pH @ 20°C:	7.6 (10.0% solution)	

## 

### **Stability and Reactivity**

Stability:	Stable under ordinary conditions of use and storage.
Incompatibilities:	Organic solvent
Materials to Avoid: Hazardous Decomposition	Strong acid or alkali and oxidant Boron compounds produced
Decomposition Products:	

### **Toxicological Information**

Acute Toxicity: Ingestion: Skin/Dermal:	Low acute oral toxicity; LD50 in rats is > 20,000 mg/kg of body weight. Low acute dermal toxicity; LD50 in rabbits is greater than 20,000 mg/kg of body weight. ProTEKtor IID® is poorly absorbed through intact skin.
Skin irritation:	Non-irritant
Eye irritation:	Draize test in rabbits produced mild eye irritation effects. Years of occupational exposure to ProTEKtor IID <sup>®</sup> indicates no adverse effects on the human eye; therefore ProTEKtor IID <sup>®</sup> is not considered to be a human-eye irritant in normal industrial use.
Sensitization:	ProTEKtor IID <sup>®</sup> not a skin sensitizer.
Human Data:	Human epidemiological studies show no increase in pulmonary disease in occupational populations with chronic exposures to boric acid dusts and sodium borate dusts. A recent epidemiology study under the conditions of normal occupational exposure to borate dusts indicated no effect on fertility.
Carcinogenicity:	Anhydrous Disodium Octaborate is not found in the following lists: FEDERAL OSHA Z LIST, NTP, IARC, CAL/OSHA, and therefore is NOT considered to be, or suspected to be, a cancer-causing agent by these agencies.

Irritancy of Product:	Dusts generated by this product may be mildly irritating to contaminated tissues.	01
Sensitization of Product:	The product is not reported to cause sensitization effects in humans after prolonged or repeated exposures.	02 03
Reproductive Toxicity Information:	Listed below is information concerning the effects of this product and its components on the human reproductive systems.	04 05
	<ul> <li>Mutagenicity: This product is not reported to produce mutagenic effects in humans.</li> <li>Embryotoxicity: This product is not reported to produce embryotoxic effects in humans.</li> <li>Teratogenicity: This product is not reported to cause teratogenic effects in humans.</li> <li>Reproductive Effects: This product is not reported to cause cause reproductive effects in humans.</li> </ul>	
ACGIH Biological Exposure Indices (Beis):	Currently, there are no ACGIH Biological Exposure Indices associated with the components of this product.	
Medical Conditions Aggravated by Exposure:	Skin disorders may be aggravated by exposure to this product. Overexposures to dusts of this product may aggravate respiratory conditions.	
Recommendations to Physicians:	Treat symptoms and eliminate overexposure.	

### **Ecological Information**

Ecotoxicity Data General:	Boron (B) is the element in disodium octaborate tetrahydrate (ProTEKtor IID®) which is used by convention to report borate product ecological effects. It occurs naturally in seawater at an average concentration of 5 mg B/L and generally occurs in freshwater at concentrations up to 1 mg B/L. In dilute aqueous solutions the predominant boron species present is undissociated boric acid. To convert disodium octaborate tetrahydrate into the equivalent boron (B) content, multiply by 0.2096.
Phytotoxicity:	Boron is an essential micronutrient for healthy growth of plants; however, it can be harmful to boron sensitive plants (e.g. grass and ornamentals) in high quantities. Care should be taken to minimize the amount of ProTEKtor IID <sup>®</sup> accidentally spilled and released into the environment.
Algal Toxicity:	Green algae, Scenedesmus subspicatus 96-hr EC10 = 24 mg B/L <sup>t</sup>
Invertebrate Toxicity <sup>8</sup> :	Daphnids, Daphnia magna straus 24-hr EC50 = 242 mg B/L <sup>t</sup>
Test substance based on:	<sup>t</sup> sodium tetraborate (not diluted)

Fish Toxicity:	Seawater9:	01
	Dab, Limanda limanda	
	96-hr LC50 = 74mg B/L <sup>t</sup>	02
	Freshwater <sup>10</sup> :	03
	Rainbow trout, S gairdneri (embryo-larval stage)	
	24-day, LC50 = 88mg B/L <sup>t</sup>	04

Goldfish, Carassius auratus (embryo-larval stage)

32-day, LC50 = 54mg  $B/L^t$ 

7-day, LC50 = 65mg B/L<sup>t</sup>

3-day, LC50 = 71mg B/L<sup>t</sup>

#### **Environmental Fate Data**

Persistence/	Boron is naturally occurring and ubiquitous in the
Degradation:	environment. ProTEKtor IID <sup>®</sup> decomposes in the environment to natural borate.
Octanol/Water Partition Coefficient:	No value. In aqueous solution disodium octaborate tetrahydrate is converted substantially into undissociated boric acid.
Soil Mobility:	ProTEKtor IID <sup>®</sup> is a water soluble liquid and is leachable through normal soil.

### **Disposal Considerations**

Preparing Wastes for Disposal:	appropriate U.S. Federal, State and local regulations,	04
U.S. EPA Waste Number:	U.S. Epa Waste Number: Not applicable to wastes consisting only of this product.	
Pesticide Disposal:	Pesticide wastes are considered to be acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use, according to the label instruction, contact the appropriate U.S. States Pesticide or Environment Control Agency, the Hazardous Waste Representative at the nearest EPA Regional Office, or the offices of Environment Canada for guidance.	
Container Disposal:	If necessary, triple rinse (or equivalent), then offer the container for recycling or reconditioning. Alternatively, puncture the container and dispose of in a procedure approved by local authorities.	

Disposal Guidance:	Small quantities of ProTEKtor IID <sup>®</sup> can usually be	01
	disposed of at landfill sites. No special disposal	
	treatment is required, but local authorities should	02
	be consulted about any specific local requirements.	
	Tonnage quantities of product are not	03
	recommended to be sent to landfills. Such products	
	should, if possible, be used for an appropriate	04
	application.	
		05
RCRA (40 CFR 261):	ProTEKtor IID <sup>®</sup> is not listed under any sections of the	
	Federal Resource Conservation and Recovery Act	
	(RCRA).	
NPRI (Canada):	ProTEKtor IID <sup>®</sup> is not listed on the Canadian National	
	Pollutant Release Inventory.	

Refer to Section 15 for additional regulatory information.

### **Transportation Information**

DOT Hazardous Classification:	Disodium octaborate tetrahydrate (ProTEKtor IID®) is not regulated by the U.S. Department of Transportation (DOT) and is therefore not considered a hazardous material/substance.	04 05
TDG Canadian Transportation:	Disodium octaborate tetrahydrate (ProTEKtor IID®) is not regulated under Transportation of Dangerous Goods (TDG).	
WHMIS Classification:	Disodium octaborate tetrahydrate (ProTEKtor IID®) is classified as Class D – Division 2A under Canadian WHMIS guidelines.	
International Transportation:	Disodium octaborate tetrahydrate (ProTEKtor IID®) has no UN Number, and is not regulated under international rail, road, water or air transport regulations.	

n	3
U	4

Regulatory Ir	nformation
FIFRA:	ProTEKtor IID <sup>®</sup> is registered with the EPA (EPA Reg. No. 1624-39), in accordance with Section 3 of the Federal Professional, Fungicide and Rodenticide Act (FIFRA), as a
	pesticide product. Refer to EPA approved product label for additional product hazard and precautionary information.
Canadian PCP:	ProTEKtor IID <sup>®</sup> is registered with Health Canada's Pest Management Regulatory Agency (PMRA) under the Pest Control Products Act (PCP) (PCP Reg. No. 24091).
Chemical Inventory Listing:	Disodium octaborate tetrahydrate (ProTEKtor IID®), 12280-03-4, appears on several chemical inventory lists (including the EPA TSCA inventory, Canadian DSL, European EINECS and Korean lists) under the CAS No. representing the anhydrous form of this inorganic salt. <b>South Korea</b> 9312-3213
RCRA:	Disodium octaborate tetrahydrate is not listed as a hazardous waste under any sections of the Resource Conservation and Recovery Act (RCRA) or regulations (40 CFR 261 et seq).

California Proposition 65:	Disodium octaborate tetrahydrate (ProTEKtor IID®) is not listed on the Proposition 65 list of carcinogens or reproductive toxicants.	<b>01</b> 02
Superfund:	CERCLA/SARA. Disodium octaborate tetrahydrate is not listed under CERCLA or its 1986 amendments, SARA, including substances listed under Section 313 of SARA, Toxic Chemicals, 42 USC 11023, 40 CFR 372.65, Section 302 of SARA, Extremely Hazardous Substances, 42 USC 11002, 40 CFR 355, or the CERCLA Hazardous Substances list, 42 USC 9604, 40 CFR 302.	03 04 05
Safe Drinking Water Act (SDWA):	Disodium octaborate tetrahydrate is not regulated under the SDWA, 42 USC 300g-1, 40 CFR 141 et seq. Consult state and local regulations for possible water quality advisories regarding boron compounds.	
Clean Water Act (CWA) (Federal Water Pollution Control Act):	<ul> <li>a) Disodium octaborate tetrahydrate (ProTEKtor IID<sup>®</sup>) is not itself a discharge covered by any water quality criteria of Section 304 of the CWA, 33 USC 1314.</li> <li>b) It is not on the Section 307 List of Priority Pollutants, 33 USC 1317, 40 CFR 129.</li> <li>c) It is not on the Section 311 List of Hazardous Substances, 33 USC 1321, 40 CFR 116.</li> </ul>	
Canadian Drinking Water Guideline:	An "Interim Maximum Acceptable Concentration" (IMAC) for boron is currently set at 5 mg B/L	

IARC:	The International Agency for Research on Cancer (IARC, a unit of the World Health Organization) does	01
	not list or categorize disodium octaborate	02
	tetrahydrate as a carcinogen.	
		03
NTP Biennial Report	Disodium octaborate tetrahydrate is not listed.	
on Carcinogens:		04
OSHA Carcinogen:	Disodium octaborate tetrahydrate is not listed.	05
Clean Air Act	ProTEKtor IID <sup>®</sup> was not manufactured with and does	
(Montreal Protocol):	not contain any Class I or Class II ozone-depleting	
	substances.	

**References:** 

### **Other Information**

01

#### 03

#### 04

05

- 1. Litovitz T L, Norman S A, Veltri J C, Annual Report of the American Association of Poison Control Centers Data Collection System. Am. J. Emerg. Med. 4: 427-458 (1986).
- 2. Weir R J, Fisher R S, Toxicol. Appl. Pharmacol. 23: 351-364 (1972).
- 3. Fail et al., Fund. Appl. Toxicol. 17: 225-239 (1991).
- 4. Price et al., J. Am. Coll. Toxicol. 14: (2), 173 (Abst. P-17) (1995).
- 5. Murray F J, Regul. Toxicol. Pharmacol. (Dec. 1995).
- National Toxicology Program (NTP)—Toxicology and carcinogenesis studies of boric acid in B6C3F1 mice, Tech. Report Ser. No. 324, U.S. Dept. of Health and Human Services. NIH Publ. No. 88-2580 (1987).
- 7. Whorton et al., Occup. Environ. Med. 51: 761-767 (1994).
- 8. Schoberl et al., Tenside Surfactants Detergents 25: 99-107 (1988).
- 9. Hugman S J, Mance G, Water Research Centre Report 616-M (1983).
- 10. Butterwick L, de Oude N, Raymond K, Ecotoxicol. Environ. Safety 17: 339-371 (1989).

For general information on the toxicology of inorganic borates, see Patty's Industrial Hygiene and Toxicology, 4th Ed. Vol. II, (1994), Chap. 42, Boron; ECETOC Tech. Report No. 63 (1995).

Date of Issue: January 21, 2021 (Revision 002)

June 18, 2018

Information contained in this SDS refers only to the specific material designated and does not relate to any process or use with any other materials. This information is furnished free of charge and is based on data believed to be reliable as of the date hereof. It is intended for use by persons possessing technical knowledge at their own discretion and risk. Since actual use is beyond our control, no guarantee, expressed or implied, and no liability is assumed by BarrierTek Inc., in conjunction with the use of this information. Nothing herein is to be construed as a recommendation to infringe any patents.

## **ProTEKtor IIJ**®

**Technical Data Sheets** 





# **ProTEKtor IIJ®** Technical Data Sheet

### **Intumescent Latex Paint**

#### **Intended Uses:**

01	A fire-resistant latex paint specifically designed for use on wood
02	substrates in attics or other confined spaces to reduce flame spread and smoke development. For interior use.
03	Product Description:
04	A high solids latex coating containing pigments and fillers with low
05	VOC levels (less than 5 g/l)

Date of Issue:

January 21, 2021

<b>Finish:</b> Flat	<b>Standard Colours:</b> Green or Blue	
<b>Tint Range:</b> Any colour in pastels	<b>Secondary Colours:</b> N/A	
<b>Required Coverage:</b> 32.8 grams / ft <sup>2</sup>	<b>Typical Volume Solids:</b> 62%	
<b>Recommended # of Coats:</b> 1 at recommended coverage	<b>Typical Specific Gravity:</b> 1.2	
<b>Flash Point:</b> N/A	Application Thinner: DO NOT THIN	

Flame Spread Index: 10 (CAN/ULC S102)

Smoke Development Index: 50 (CAN/ULC S102)

#### **Surface Preparation**

Surfaces must be clean, dry, and free of dust and other debris. Remove any loose substrate pieces (i.e. wood, peeling paint). When treating bare wood surfaces with the intent of fire protection, no priming is required. When treating raw drywall, apply a prime coat.

#### Application

Brush, roller, or suitable heavy-duty airless sprayer. (Recommended tips are .20-.30 inches.)

Dry times at 21°C and 50% (+ or – 10) R.H. **To Touch:** 45 minutes – 2 hours **To Handle:** 3 – 5 hours **To Overcoat:** 6 hours minimum

#### **Additional Data**

For optimum adhesion and application performance, ensure that the temperature and relative humidity are between 15 and 25°C and 40-60% respectively, at the time of application and for four hours afterward.

The information provided is accurate and true to the best of our knowledge. However, no guarantee or warranty of any kind, expressed or implied, is given when the product is not applied by certified BarrierTek Inc. installers.

## **ProTEKtor IIJ**®

Safety Data Sheet

## **01** Identification

**Product Name: ProTEKtor IIJ® Product Code:** \_\_\_\_\_ **Product Use: Fire Retardant** Manufacturer's Name: BarrierTek 7123 Sparrow Dr Leduc, Alberta, Canada T9E 7L1 **BarrierTek Phone:** (780) 612-7740 In case of hazardous materials or dangerous goods **Emergency Phone:** incident, spill, leak, fire, exposure, or accident, call CHEMTREC 24 hours at 1-800-242-9300 or 1-703-527-3887. **SDS Preparation Date:** January 2021

01

02

03


04

### Hazard Identification Toxicological Properties

Hazard Classification:	Skin irritation Cat.3, Eye irritation Cat.2B	05		
Warning Information:	None			
Pictogram:	None			
Signal Words:	Warning			
Hazard Statement:	May be harmful if swallowed.			
	May be harmful if inhaled.			
	May cause mild skin irritation.			
	May cause eye irritation.			
Precautions:	<ol> <li>Avoid contact with eyes. If contact with eyes, wash immediately with plenty of water and seek medical attention.</li> <li>Avoid contact with skin. Exposure to product may result in skin irritation.</li> <li>Do not ingest. Swallowing may cause stomach upset and vomiting.</li> <li>Wear protective clothing and gloves when working with product.</li> </ol>			

### Composition / Information on Ingredients

Ingredients	CAS #	% Percent (by weight)	Hazard Classification
Acrylic Copolymer	Intellectual Property	20-30	None
Ammonium Polyphosphate	68333-79-9	10-20	H315, H320, H335
Water		20-30	None
Titanium Dioxide	13463-67-7	<2	H351



### **Fire-Fighting Measures**

Fire:	Fire Resistant	04
Explosion:	Not considered to be an explosion hazard	05
Fire Extinguishing Media:	Not Required	
Firefighting Procedures:	Firefighters must wear proper protective equipment including a breathing apparatus with oxygen supply.	
Protective Equipment for Firefighters:	Firefighters must wear a breathing apparatus, fire protective clothing, and gloves.	

## 

### **Accidental Release Measures**

Personnel Precautions:	Wear appropriate personal protective equipment.		
Environmental Precautions:	<ol> <li>Ventilate area.</li> <li>Keep contaminants from entering sewers.</li> </ol>		
Clean Up:			
	Contain large spills with sand or soil. When chemical		
	is absorbed, dispose of the sand or soil. Remove		
	any residue from the area.		

### Handling and Storage Procedures

- Containers must be properly labeled and closed 05 when not in use.
- 2. Keep readily available to deal with the fire and emergency response device leakage.
- 3. Place in a cool, dry area, away from heat, sparks, and cold.

## 08

### Exposure Controls: Personal Protection

Engineering Control:	N/A
Control Factor:	N/A
Personal Respirators:	N/A
Skin Protection:	Wear protective gloves.
Eye Protection:	Wear safety glasses or goggles.

01

02

03

### **Physical and Chemical Properties**

		04
Colour:	Green or Blue	
Odor:	N/A	05
Safety Data:	Flash Point: N/A	00
	Ignition temperature: N/A	
	Self-ignition temperature: N/A	
	Lower explosion limit: N/A	
	Upper explosion limit: N/A	
Solubility:	Water miscible	
Density:	1.2	
PH:	7-9	
Viscosity:	2500-3500	
Solid Content:	62%	

## 

### **Stability and Reactivity**

Stability:	Stable under ordinary conditions of use and storage.
Incompatibilities:	Organic solvent
Materials to Avoid:	Strong acid or alkali and oxidant
Hazardous Decomposition	Will emit smoke, CO, CO2 when on fire.
Products:	

### **Toxicological Information**

Acute Oral Toxicity (LD50):N/ASub-chronic Effects:N/AChronic Toxicity or LongN/ATerm Toxicity:X

### **Ecological Information**

Ecological Effect:
Environmental Effects:

Fish toxicity (LC50); None Do not dispose of this product into the sewer water or into soil.

## 13

### **Disposal Considerations**

Dispose of waste in sanitary landfill or by incineration in accordance with regulations.

02

03

04

Transportation Information		
International Regulations:	Not a hazardous or restricted item for transport by road, rail, sea or air.	04 05
Transportation Summary:	These products are not regulated as hazardous materials.	05
UN Classification Number:	N/A	
IMDG Code & Package	None	
Group:		
Marine Pollutant:	N/A	
Specific Precautionary		
Transport Measures and	N/A	
Conditions:		

## 15

### **Regulatory Information**

Health Hazardous Goods:NoEnvironmental HazardousNoGoods:Fire Hazardous Goods:No


Information contained in this SDS refers only to the specific material designated and does not relate to any process or use with any other materials. This information is furnished free of charge and is based on data believed to be reliable as of the date hereof. It is intended for use by persons possessing technical knowledge at their own discretion and risk. Since actual use is beyond our control, no guarantee, expressed or implied, and no liability is assumed by BarrierTek Inc., in conjunction with the use of this information. Nothing herein is to be construed as a recommendation to infringe any patents.

01

กา

# **ProTEKtor® (PG)**

**Technical Data Sheets** 



# **ProTEKtor® (PG)** Technical Data Sheet

# /04

## **Intumescent Latex Paint**

#### **Intended Uses:**

01	A fire-resistant latex paint specifically designed for use on wood
	substrates in attics or other confined spaces to reduce flame spread
02	and smoke development. For interior use.
03	
03	Product Description:
04	A high solids latex coating containing pigments and fillers with low
	VOC levels (less than 5 g/l)
05	

Date of Issue:

January 21, 2021

Finish: Flat	Standard Colours: Green or Blue	
<b>Tint Range:</b> Any colour in pastels	<b>Secondary Colours:</b> By special request only	
<b>Required Coverage:</b> 32.8 grams / ft² (140 ft²/gallon)	<b>Typical Volume Solids:</b> 62%	
<b>Recommended # of Coats:</b> 1 at recommended coverage	<b>Typical Specific Gravity:</b> 1.2	
<b>Flash Point:</b> N/A	Application Thinner: DO NOT THIN	

Flame Spread Index: 10 (CAN/ULC S102)

Smoke Development Index: 65 (CAN/ULC S102)

#### **Surface Preparation**

Surfaces must be clean, dry, and free of dust and other debris. Remove any loose substrate pieces (i.e. wood, peeling paint). When treating bare wood surfaces with the intent of fire protection, no priming is required. When treating raw drywall, apply a prime coat.

#### Application

Brush, roller, or suitable heavy-duty airless sprayer. (Recommended tips are .20-.30 inches.)

Dry times at 21°C and 50% (+ or – 10) R.H. **To Touch:** 45 minutes – 2 hours **To Handle:** 3 – 5 hours **To Overcoat:** 6 hours minimum

#### **Additional Data**

For optimum adhesion and application performance, ensure that the temperature and relative humidity are between 15 and 25°C and 40-60% respectively, at the time of application and for four hours afterward.

The information provided is accurate and true to the best of our knowledge. However, no guarantee or warranty of any kind, expressed or implied, is given when the product is not applied by certified BarrierTek Inc. installers.

# **ProTEKtor® (PG)**

Safety Data Sheet

# 01

03 04

01

02

05

# **Identification**

**Product Name: ProTEKtor**® **Product Code:** \_\_\_\_\_ **Product Use: Fire Retardant** Manufacturer's Name: BarrierTek 7123 Sparrow Dr Leduc, Alberta, Canada T9E 7L1 **BarrierTek Phone:** (780) 612-7740 **Emergency Phone:** In case of hazardous materials or dangerous goods incident, spill, leak, fire, exposure, or accident, call CHEMTREC 24 hours at 1-800-242-9300 or 1-703-527-3887. **SDS Preparation Date:** September 2020

## Hazard Identification Toxicological Properties

Hazard Classification:	Skin irritation Cat.3, Eye irritation Cat.2B		
Warning Information:	None		
Pictogram:	None		
Signal Words:	Warning		
Hazard Statement:	May be harmful if swallowed.		
	May be harmful if inhaled.		
	May cause mild skin irritation.		
	May cause eye irritation.		
Precautions:	<ol> <li>Avoid contact with eyes. If contact with eyes, wash immediately with plenty of water and seek medical attention.</li> </ol>		
	2. Avoid contact with skin. Exposure to product may result in skin irritation.		
	3. Do not ingest. Swallowing may cause stomach upset and vomiting.		
	4. Wear protective clothing and gloves when working with product.		

## Composition / Information on Ingredients

Ingredients	CAS #	% Percent (by weight)	Hazard Classification
Acrylic Copolymer	Intellectual Property	20-30	None
Ammonium Polyphosphate	68333-79-9	10-20	H315, H320, H335
Water		20-30	None
Titanium Dioxide	13463-67-7	<2	H351

<b>04</b> First Aid	
Eye Contact:	Flush eyes gently with water for 10-15 minutes. Flush gently under the upper and lower eyelids. If experiencing painful, irritated or watery eyes, redness or swelling in or around the eyes, or other discomfort, seek medical attention immediately.
Skin Contact:	Thoroughly wash affected area with soap and warm water. Then rinse with warm water for 15 minutes. If rash or skin irritation occurs, seek medical attention immediately.
Inhalation:	If dizziness occurs, move outside or into a well-ventilated space immediately. If dizziness persists, seek medical attention.
Ingestion:	If product is ingested, drink 1-2 cups of water and seek medical attention immediately.
General Guidance:	If feeling unwell, seek medical attention. If possible, show the product label and this safety sheet to medical personnel. Tell medical personnel what chemicals were involved.

## **Fire-Fighting Measures**

		04
Fire:	Fire Resistant	04
Explosion:	Not considered to be an explosion hazard	05
Fire Extinguishing Media:	Not Required	0.
Firefighting Procedures:	Firefighters must wear proper protective equipment	
	including a breathing apparatus with oxygen supply.	
Protective Equipment for	Firefighters must wear a breathing apparatus, fire	
Firefighters:	protective clothing, and gloves.	

## 

#### **Accidental Release Measures**

Personnel Precautions:	Wear appropriate personal protective equipment.
Environmental	1. Ventilate area.
Precautions:	2. Keep contaminants from entering sewers.
Clean Up:	Contain large spills with sand or soil. When chemical is absorbed, dispose of the sand or soil. Remove any residue from the area.

## Handling and Storage Procedures

- Containers must be properly labeled and closed when not in use.
- 2. Keep readily available to deal with the fire and emergency response device leakage.
- 3. Place in a cool, dry area, away from heat, sparks, and cold.

# 08

## Exposure Controls: Personal Protection

Engineering Control:	N/A
Control Factor:	N/A
Personal Respirators:	N/A
Skin Protection:	Wear protective gloves.
Eye Protection:	Wear safety glasses or goggles.

03

02

## **Physical and Chemical Properties**

		04
Colour:	Green or Blue	01
Odor:	N/A	05
Safety Data:	Flash Point: N/A	
	Ignition temperature: N/A	
	Self-ignition temperature: N/A	
	Lower explosion limit: N/A	
	Upper explosion limit: N/A	
Solubility:	Water miscible	
Density:	1.2	
PH:	7-9	
Viscosity:	2500-3500	
Solid Content:	62%	

## 

## **Stability and Reactivity**

Stability:	Stable under ordinary conditions of use and storage.
Incompatibilities:	Organic solvent
Materials to Avoid:	Strong acid or alkali and oxidant
Hazardous Decomposition	Will emit smoke, CO, CO2 when on fire.
Products:	

## **Toxicological Information**

Acute Oral Toxicity (LD50):N/ASub-chronic Effects:N/AChronic Toxicity or LongN/ATerm Toxicity:

## 12

#### **Ecological Information**

Ecological Effect:	
Environmental Effects:	

Fish toxicity (LC50); None Do not dispose of this product into the sewer water or into soil.

## 13

#### **Disposal Considerations**

Dispose of waste in sanitary landfill or by incineration in accordance with regulations.

02

03

04

Transportation Information		02	
		03	
International Regulations:	Not a hazardous or restricted item for transport by road, rail, sea or air.	04 05	
Transportation Summary:	These products are not regulated as hazardous materials.	05	
<b>UN Classification Number:</b>	N/A		
IMDG Code & Package	None		
Group:			
Marine Pollutant:	N/A		
Specific Precautionary	N/A		
Transport Measures and			
Conditions:			



#### **Regulatory Information**


Health Hazardous Goods:NoEnvironmental HazardousNoGoods:Fire Hazardous Goods:No

Information contained in this SDS refers only to the specific material designated and does not relate to any process or use with any other materials. This information is furnished free of charge and is based on data believed to be reliable as of the date hereof. It is intended for use by persons possessing technical knowledge at their own discretion and risk. Since actual use is beyond our control, no guarantee, expressed or implied, and no liability is assumed by BarrierTek Inc., in conjunction with the use of this information. Nothing herein is to be construed as a recommendation to infringe any patents.

01



**Technical Data Sheets** 



# **AtTEK**<sup>®</sup>

## **Technical Data Sheet**

# /05

#### **Intumescent Latex Paint**

#### **Intended Uses:**

01	A fire-resistant latex paint specifically designed for use on wood
02	substrates in attics or other confined spaces to reduce flame spread and smoke development. For interior use.
03	Product Description:
04	A high solids latex coating containing pigments and fillers with low VOC levels (less than 5 g/l)
05	

Date of Issue:

October 15, 2014

<b>Finish:</b> Flat	<b>Standard Colours:</b> Orange (stock)	
<b>Tint Range:</b> Any colour in pastels	Secondary Colours: By special request only	
<b>Required Coverage:</b> 80 grams / ft <sup>2</sup>   61 ft <sup>2</sup> / gallon   18.3 Wet Mils	<b>Typical Volume Solids:</b> 68%	
<b>Recommended # of Coats:</b> 1 – 2 at recommended coverage	<b>Typical Specific Gravity:</b> 1.3	
<b>Flash Point:</b> N/A	<b>Application Thinner:</b> DO NOT THIN	

Flame Spread Index: 0 (ASTM E84 - 30 minute extended)

\*\*flame front did not propagate beyond 10'6" for the 30 minute duration of the test (ASTM E2768)
Smoke Development Index: 50 (ASTM E84 – 30 minute extended)

#### **Surface Preparation**

Surfaces must be clean, dry, and free of dust and other debris. Remove any loose substrate pieces (i.e. wood, peeling paint). When treating bare wood surfaces with the intent of fire protection, no priming is required. When treating raw drywall, apply a prime coat.

#### Application

Brush, roller, or suitable heavy-duty airless sprayer. (Recommended tips are .20-.30 inches.)

Dry times at 21°C and 50% (+ or – 10) R.H. **To Touch:** 45 minutes – 2 hours **To Handle:** 3 – 5 hours **To Overcoat:** 6 hours minimum

#### **Additional Data**

For optimum adhesion and application performance, ensure that the temperature and relative humidity are between 15 and 25°C, and 40-60% respectively, at the time of application and for four hours afterward. If the temperature is below 5°C, a specially-formulated winter version of AT is available that will cure and properly adhere up to -10°C.

The information provided is accurate and true to the best of our knowledge. However, no guarantee or warranty of any kind, expressed or implied, is given when the product is not applied by certified BarrierTek Inc. installers.



Safety Data Sheet

# 01 02 03 04

05

## **01** Identification

**Product Name: AtTEK**<sup>®</sup> **Product Code:** -----**Product Use: Fire Retardant** Manufacturer's Name: **BarrierTek** 7123 Sparrow Dr Leduc, Alberta, Canada T9E 7L1 **BarrierTek Phone:** (780) 612-7740 **Emergency Phone:** In case of hazardous materials or dangerous goods incident, spill, leak, fire, exposure, or accident, call CHEMTREC 24 hours at 1-800-242-9300 or 1-703-527-3887. **SDS Preparation Date:** September 2020

## Hazard Identification Toxicological Properties

Hazard Classification:	Skin irritation Cat.3, Eye irritation Cat.2B 0
Warning Information:	None
Pictogram:	None
Signal Words:	Warning
Hazard Statement:	May be harmful if swallowed.
	May be harmful if inhaled.
	May cause mild skin irritation.
	May cause eye irritation.
<b>Precautions:</b>	<ol> <li>Avoid contact with eyes. If contact with eyes, wash immediately with plenty of water and seek medical attention.</li> <li>Avoid contact with skin. Exposure to product may result in skin irritation.</li> <li>Do not ingest. Swallowing may cause stomach upset and vomiting.</li> <li>Wear protective clothing and gloves when working with product.</li> </ol>

## Composition / Information on Ingredients

Ingredients	CAS #	% Percent (by weight)	Hazard Classification
Acrylic Copolymer	Intellectual Property	20-30	None
Ammonium Polyphosphate	68333-79-9	10-20	H315, H320, H335
Water		20-30	None
Titanium Dioxide	13463-67-7	<2	H351

04
First Aid

Eye Contact:	Flush eyes gently with water for 10-15 minutes. Flush gently under the upper and lower eyelids. If experiencing painful, irritated or watery eyes, redness or swelling in or around the eyes, or other discomfort, seek medical attention immediately.
Skin Contact:	Thoroughly wash affected area with soap and warm water. Then rinse with warm water for 15 minutes. If rash or skin irritation occurs, seek medical attention immediately.
Inhalation:	If dizziness occurs, move outside or into a well-ventilated space immediately. If dizziness persists, seek medical attention.
Ingestion:	If product is ingested, drink 1-2 cups of water and seek medical attention immediately.
General Guidance:	If feeling unwell, seek medical attention. If possible, show the product label and this safety sheet to medical personnel. Tell medical personnel what chemicals were involved.

## **Fire-Fighting Measures**

Fire Resistant	04
Not considered to be an explosion hazard	0.5
Not Required	05
Firefighters must wear proper protective equipment	
including a breathing apparatus with oxygen supply.	
Firefighters must wear a breathing apparatus, fire	
protective clothing, and gloves.	
	Not considered to be an explosion hazard Not Required Firefighters must wear proper protective equipment including a breathing apparatus with oxygen supply. Firefighters must wear a breathing apparatus, fire

## 

#### **Accidental Release Measures**

Personnel Precautions:	Wear appropriate personal protective equipment.
Environmental Precautions:	<ol> <li>Ventilate area.</li> <li>Keep contaminants from entering sewers.</li> </ol>
Clean Up:	Contain large spills with sand or soil. When chemical is absorbed, dispose of the sand or soil. Remove any residue from the area.

## Handling and Storage Procedures

- 1. Containers must be properly labeled and closed when not in use.
- 2. Keep readily available to deal with the fire and emergency response device leakage.
- 3. Place in a cool, dry area, away from heat, sparks, and cold.

## 08

#### Exposure Controls: Personal Protection

Engineering Control:	N/A
Control Factor:	N/A
Personal Respirators:	N/A
Skin Protection:	Wear protective gloves.
Eye Protection:	Wear safety glasses or goggles.

01

02

03

04

## **Physical and Chemical Properties**

Orange

N/A

01

04

- -

05

Odor:
Safety Data:

**Colour:** 

Solubility: Density: PH: Viscosity: Solid Content: Flash Point: N/A Ignition temperature: N/A Self-ignition temperature: N/A Lower explosion limit: N/A Upper explosion limit: N/A Water miscible 1.2 7-9 2500-3500 62%

## 10

## **Stability and Reactivity**

Stability:Stable under ordinary conditions of use and storage.Incompatibilities:Organic solventMaterials to Avoid:Strong acid or alkali and oxidantHazardous DecompositionWill emit smoke, CO, CO2 when on fire.Products:Content of the strong action of the s

## **Toxicological Information**

Acute Oral Toxicity (LD50):N/ASub-chronic Effects:N/AChronic Toxicity or LongN/ATerm Toxicity:X

## 

### **Ecological Information**

Ecological Effect:	Fish toxicity (LC50); None
Environmental Effects:	Do not dispose of this product into the sewer water or
	into soil.

## 

#### **Disposal Considerations**

Dispose of waste in sanitary landfill or by incineration in accordance with regulations.

Transportation Information		02
		03
International Regulations:	Not a hazardous or restricted item for transport by road, rail, sea or air.	04
Transportation Summary:	These products are not regulated as hazardous materials.	05
<b>UN Classification Number:</b>	N/A	
IMDG Code & Package	None	
Group:		
Marine Pollutant:	N/A	
Specific Precautionary	N/A	
Transport Measures and		
Conditions:		

## 

#### **Regulatory Information**

Health Hazardous Goods:	No
Environmental Hazardous	No
Goods:	
Fire Hazardous Goods:	No

Information contained in this SDS refers only to the specific material designated and does not relate to any process or use with any other materials. This information is furnished free of charge and is based on data believed to be reliable as of the date hereof. It is intended for use by persons possessing technical knowledge at their own discretion and risk. Since actual use is beyond our control, no guarantee, expressed or implied, and no liability is assumed by BarrierTek Inc. , in conjunction with the use of this information. Nothing herein is to be construed as a recommendation to infringe any patents.